










Gase vom Mittelstand für den Mittelstand

Gasart	Größen	Inhalt	Gewicht	UN-Nummer	ADR-Pkt.	Ventilanschluß	Farbgebung	Schulterfarbe
Argon 4.6	C5	1 m ³	10 kg	UN 1006	5	W 21,8x1/14" 25 E, GK DIN 477 Nr. 6	RAL 6001 dunkelgrün DIN EN 1089-3	
	C10	2,1 m ³	15 kg		10			
	C20	4,3 m ³	25 kg		20			
	C50	10,7 m ³	70 kg		50			
Mix 18 (Ar82 % + Co2 18%)	C5	1,2 m ³	10 kg	UN 1956	5	W 21,8x1/14" 25 E, GK DIN 477 Nr. 6	RAL 6018 hellgrün DIN EN 1089-3	
	C10	2,4 m ³	15 kg		10			
	C20	4,7 m ³	22 kg		20			
	C50	11,8 m ³	70 kg		50			
Sauerstoff	C5	1 m ³	10 kg	UN 1072	5	G 3/4 " 25 E, GK DIN 477 Nr. 9	RAL 9010 reinweiss DIN EN 1089-3	
	C10	2 m ³	15 kg		10			
	C20	4 m ³	25 kg		20			
	C50	10 m ³	70 kg		50			
Acetylen	C5	0,8 kg	18 kg	UN 1001	2,4	Bügelanschluß M 15, x 7,5 DIN 477 Nr. 3	RAL 3009 kastanienbraun DIN EN 1089-3	
	C10	1,6 kg	22 kg		4,8			
	C20	4,0 kg	35 kg		12			
	C50	10 kg	80 kg		30			
Stickstoff	C5	1 m ³	10 kg	UN 1066	5	W 24,32x1/14" 25 E, GK DIN 477 Nr. 10	RAL 9005 tiefschwarz DIN EN 1089-3	
	C10	2 m ³	15 kg		10			
	C20	4 m ³	25 kg		20			
	C50	10 m ³	70 kg		50			
Helium	C5	0,9 m ³	10 kg	UN 1046	5	W 21,8x1/14" 25 E, GK DIN 477 Nr. 6	RAL 8008 olivbraun DIN EN 1089-3	
	C10	1,8 m ³	15 kg		10			
	C20	3,6 m ³	25 kg		20			
	C50	9,1 m ³	70 kg		50			
Kohlensäure	C 2,7	2 kg	8 kg	UN 1013	2	W 21,8x1/14" 25 E, GK DIN 477 Nr.6	RAL 7037 staubgrau DIN EN 1089-3	
	C 8	6 kg	20 kg		6			
	C 13,4	10 kg	25 kg		10			
	C 50	37,5 kg	85 kg		37,5			
Wasserstoff	C10	1,9 m ³	15 kg	UN 1049	30	W 21,8x1/14" LH 25 E, GK DIN 477 Nr.1	RAL 3000 rot DIN EN 1089-3	
	C50	8,9 m ³	70 kg		150			
Fomiergas	C10	1,9 m ³	15 kg	UN 1954	30	W 21,8x1/14" LH 25 E, GK DIN 477 Nr.1	RAL 3000 rot DIN EN 1089-3	
	C50	9,4 m ³	70 kg		150			

